



MOTIVO COLORATO

Water-based 1C coloured coating

PRICE-PERFORMANCE WINNER

With MOTIVO COLORATO, almost any colour can be quickly and cost-effectively applied to surfaces. Good recoatability means it can also be used in combination with MOTIVO KLARLACK 2080 for top-class results. MOTIVO COLORATO is used mainly for furniture in interiors, for doors, stairs and general carpentry work.

DIVERSE PRODUCT LINE

The water-borne MOTIVO LINE for interiors is particularly quick drying. Thanks to optimum filling properties, the coloured coating is easily applied to open- and closed-pore woods and primed MDF boards. The perfectly matched product systems make it even more certain that the user achieves a high-quality application.

VERSIONS

MOTIVO COLORATO 2070 is a coloured, quick-drying top coat in all RAL and NCS S colours. MOTIVO COLORATO 2077 STRUKTUR is also a coloured coating in all RAL and NCS S colours, but in addition has a fine surface texture.

CONTACT US

Calling Teknos is a quick and easy way to get expert advice on the use of MOTIVO COLORATO or other Teknos coating products. Our technical customer service is always at your disposal when it comes to developing optimum coating solutions and systems.



MAIN FEATURES

- High UV resistance
- Easy to apply with very good levelling properties
- Quick drying with good filling properties
- Good mechanical resistance

Our mission is to extend the life of your products by providing intelligent, technically advanced paint and coating solutions for even better protection – always in close collaboration with our customers.

PRODUCT DATA

VERSIONS	<ul style="list-style-type: none">▪ MOTIVO COLORATO 2070-15▪ MOTIVO COLORATO 2070-30▪ MOTIVO COLORATO 2077-05 STRUKTUR
COLOURS	<ul style="list-style-type: none">▪ In compliance with RAL and NCS S shade cards
GLOSS LEVELS	<ul style="list-style-type: none">▪ Dull matt 05, Matt 15, Satin matt 30
APPLICATION	<ul style="list-style-type: none">▪ Gravity feed gun▪ Airless (airmix) spraying
CAN SIZE	<ul style="list-style-type: none">▪ Paint: 2.7 l and 9 l

DRYING TIMES

DUST DRY AFTER	30 MINUTES
TOUCH DRY AFTER	45 MINUTES
SANDABLE AFTER	2 HOURS
RECOATABLE AFTER	2 HOURS
FULLY DRY AFTER	10 DAYS



COATING RECOMMENDATION MOTIVO COLORATO 2070

	MDF/HDF	FOIL-LAMINATED BOARDS	WOOD
PRIMER	HYDROFILL PREMIUM 6338-00	HYDROFILL PREMIUM 6338-00	MOTIVO COLORATO 2070
INTERMEDIATE SANDING	Grain 220-240	Grain 220-240	Grain 220-240
RECOATING	MOTIVO COLORATO 2070	MOTIVO COLORATO 2070	MOTIVO COLORATO 2070

COATING RECOMMENDATION MOTIVO COLORATO 2077 STRUKTUR

	MDF/HDF	FOIL-LAMINATED BOARDS
PRIMER	HYDROFILL PREMIUM 6338-00	HYDROFILL PREMIUM 6338-00
INTERMEDIATE SANDING	Grain 220-240	Grain 220-240
RECOATING	MOTIVO COLORATO 2077 STRUKTUR	MOTIVO COLORATO 2077 STRUKTUR

For further technical information refer to technical data sheets No. 2575 and 2577.